

## Release Notes for CrossCore Embedded Studio 2.8.1

## Contents

1	Intro	oduction	3	
	1.1	1.1 Supported Operating Systems		
	1.2 System Requirements		4	
	1.3 Obtaining Technical Support			
2	Installing CrossCore Embedded Studio			
	2.1	Installing CrossCore Embedded Studio on Windows	6	
	2.2	2.2 Installing CrossCore Embedded Studio on Linux		
		2.2.1 Different users sharing the same CCES license on Linux	7	
		2.2.2 OpenOCD needs to be run as sudo on Linux	7	
3	New	and Noteworthy	8	
4	Changes That Might Impact Backwards Compatibility			
	4.1 Ethernet drivers have been updated to support the latest ADSP-SC5xx EZ-KITs			
	4.2 CMSIS support Add-ins that were deprecated in previous releases have now been removed			
5	Kno	wn Issues	11	

### **1** Introduction

This document describes the changes for CrossCore Embedded Studio (CCES) 2.8.1. You can find the release notes for older releases in the docs sub-directory of your CCES installation.

#### **1.1 Supported Operating Systems**

#### Notes for Windows Users

The following versions of Windows are supported for this release of CCES:

- Windows 7 Professional, Enterprise, or Ultimate (32 and 64-bit, SP1 or later)
- Windows 8.1 Pro or Enterprise (32 and 64-bit)
- Windows 10 Pro or Enterprise (32 and 64-bit)

#### Å Notes for Linux Users

This release of CrossCore Embedded Studio for Linux has been provided to support the Linux Add-In for CrossCore Embedded Studio and support bare-metal development on Cortex-M processors such as the ADuCM36x, ADuCM302x and ADuCM4x50 family of MCUs.

The following Linux distributions are officially supported for this release of CCES:

- Ubuntu 14.04 32-bit
- Ubuntu 16.04 32-bit

The following features are available and supported:

- Compilation using the GNU toolchain for the ARM Cortex-A core on ADSP-SC57x and ADSP-SC58x processors.
- Compilation using the GNU ARM toolchain for the ADuCM36x, ADuCM302x and ADuCM4x50 ARM Cortex-M cores.
- Debugging ADSP-SC5xx, ADuCM36x, ADuCM302x and ADuCM4x50 via the IDE with GDB/OpenOCD.
- Development and debugging of Applications running under Linux on the ARM Cortex-A core on ADSP-SC57x and ADSP-SC58x processors.
- Development and debugging of bare-metal applications on the ADuCM36x, ADuCM302x and ADuCM4x50 ARM Cortex-M cores.

The following features are only supported via the Windows version of CrossCore Embedded Studio:

- Development, simulation and debug of Blackfin processors
- Development, simulation and debug of SHARC processors (excluding the ARM Cortex-A core on ADSP-SC57x and ADSP-SC58x processors)
- Use of CrossCore Embedded Studio Add-Ins other than the Linux Add-In
- Debugging an Application using the native CrossCore Debugger

#### **1.2 System Requirements**

Verify that your PC has these minimum requirements for the CCES installation:

- 2 GHz single core processor; 3.3GHz dual core or better recommended
- 4 GB RAM; 8GB or more recommended

- 2 GB available disk space
- One open USB port

#### O Note

A faster disk drive or SSD decreases the build time, especially for a large amount of source files. 8GB of RAM or more will substantially increase the performance of the IDE.

#### **1.3 Obtaining Technical Support**

You can reach Analog Devices software and tools technical support in the following ways:

- Post your questions in the software and development tools support community at EngineerZone<sup>®</sup>
- E-mail your questions about software and development tools directly from CrossCore Embedded Studio by choosing Help > Email Support or directly to processor.tools.support@analog.com
- E-mail your questions about processors and processor applications to processor. support@analog.com
- Submit your questions to technical support directly via http://www.analog.com /support
- Contact your Analog Devices sales office or authorized distributor

## 2 Installing CrossCore Embedded Studio

#### 2.1 Installing CrossCore Embedded Studio on Windows

#### Note: Windows Only

#### ▲ Caution

Windows users may experience User Access Control (UAC) related errors if the software is installed into a protected location, such as Program Files or Program Files (x86). We recommend installing the software in a non-UAC-protected location.

#### ▲ Caution (Windows 8.1 users)

*Prior to installation:* Ensure your machine is up-to-date with relevant Windows updates from Microsoft. CrossCore Embedded Studio relies upon the Microsoft Universal C Runtime from VisualStudio 2015, and this can silently fail to install if your machine is out of date. For more details, refer to Update for Universal C Runtime in Windows on Microsoft's web site.

To install CrossCore Embedded Studio, double-click ADI\_CrossCoreEmbeddedStudio-Rel2.8.1.exe

To uninstall CrossCore Embedded Studio, open Control Panel / Programs and Features applet, and select to uninstall CrossCore Embedded Studio 2.8.1. You may need to delete the installation directory to clean up any leftover files.

#### 2.2 Installing CrossCore Embedded Studio on Linux

#### 👃 Note: Linux Only

#### ▲ Caution

It is strongly recommended to use the command prompt to install CrossCore Embedded Studio. The installation may not work properly when using Ubuntu Software and/or Ubuntu Software Center. To install CrossCore Embedded Studio run the following command from the command prompt:

```
sudo dpkg -i adi-CrossCoreEmbeddedStudio-linux-x86-2.8.1.deb
```

sudo dpkg -1 ad1-crosscoreEmbeddedStudio-11hux-x86-2.8.1.deb

To uninstall CrossCore Embedded Studio run the following commands from the command prompt:

```
sudo dpkg -r adi-cces-2.8.1
sudo dpkg -P adi-cces-2.8.1
sudo rm -rf /opt/analog/cces/2.8.1 (to clean up any leftover files)
```

#### 2.2.1 Different users sharing the same CCES license on Linux

Many users can share a single valid license.dat file on a system by creating a symbol link to the valid license.dat in their own home directory (~/.analog/cces). The user who installed license should ensure that the appropriate directory and file permissions are set-up to allow other users to access the valid license.dat.

#### 2.2.2 OpenOCD needs to be run as sudo on Linux

In order to debug an Application with GDB and OpenOCD (Emulator) on Linux, OpenOCD needs to have permissions to access your USB device. You can set-up the necessary permissions when installing CCES on Linux by selecting 'Configure OpenOCD permissions' option on the installation dialog or afterwards by running sudo sh /opt /analog/cces/2.8.1/Setup/setup\_openocd\_permissions.sh.

If you debug an Application with GDB and OpenOCD (Emulator) using the IDE and OpenOCD fails because it cannot access your USB device, a dialog will appear with a message telling you that you can run the setup\_openocd\_permissions.sh script.

If you start CCES with sudo permission, then there should be no problems with OpenOCD accessing your USB device.

## **3 New and Noteworthy**

- Ethernet drivers have been updated to support the latest ADSP-SC5xx EZ-KITs
- The license activation wizard has been updated to link to ADI's privacy policy and better conform to recent GDPR regulations in the European Union (EU).

## 4 Changes That Might Impact Backwards Compatibility

# 4.1 Ethernet drivers have been updated to support the latest ADSP-SC5xx EZ-KITs

If you are using the Ethernet Driver Add-in, then your project will be automatically upgraded, so that the new source files are now part of your project.

	Selected Ad	Selected Add-ins Advanced		
pe filter text	Name		Version	
Recommended Add-ins	↑ @Ethernet	Driver for Cortex-A	2.1.0	
Heap and Stack Configuration (1.0.0)	Heap and	Stack Configuration	1.0.0	
Analog Devices' MCAPI (1.0.0)	@Pin Multi	-	1.0.0	
Pin Multiplexing (1.0.0)		evices' MCAPI	1.0.0	
SRU Configuration (1.0.0)	SRU Con		1.0.0	
Device Drivers and System Services				
> ADSP-SC5xx EZ-Kit Off-Chip Peripheral Drivers				
🕆 🗁 On-chip peripheral drivers				
ASRC Driver for Cortex-A (1.0.0)				
CRC Driver for Cortex-A (1.0.0)				
FIR Driver for Cortex-A (1.0.0)				
FFT Driver for Cortex-A (1.0.0)				
Ethernet Driver for Cortex-A (2.1.0)				
HADC Driver for Cortex-A (1.0.0)				
HAE Driver for Cortex-A (1.0.0)				
IIR Driver for Cortex-A (1.0.0)				
Link Port Driver for Cortex-A (1.0.0)				
PPI Driver for Cortex-A (1.0.0)	~			
Advanced Filter 💿 Expand All 🔅 Collapse .	All 😑 Remove	& Quick Fix		
nernet Driver for Cortex-A(2.1.0)				
is add-in provides Analog Devices' implementation of the	ethernet driver			

#### 4.2 CMSIS support Add-ins that were deprecated in previous releases

#### have now been removed

CMSIS Pack Management added in CCES 2.5.x replaced the CMSIS support Add-ins shown in the screenshot below. Example projects and project created with CCES 2.5.x or later do not rely on the CMSIS support Add-ins.

If you are using these Add-ins, we recommend that you create a new ADuCM project which uses the CMSIS Pack Management support.

vailable Add-ins	Selected Add-ins Advanced	Selected Add-ins Advanced			
ype filter text ✓ CRecommended Add-ins ✓ Pin Multiplexing (1.0.0) ✓ CMSIS support □ CMSIS Core (deprecated) (1.0.1) □ CMSIS Device Startup for ADuCM3029 (deprecated) (1.0.1)	Name @Pin Multiplexing	Version 1.0.0			
<ul> <li>Device Drivers and System Services</li> <li>Device Drivers drivers</li> <li>System Services</li> </ul>					
Advanced Filter © Expand All @ Collaps	e All © Remove & Quick Fix				
ease expand this category to see its associated Add-ins					

## **5 Known Issues**

For the latest anomalies please consult our Software and Tools Anomalies Search page.